


DART

DESIGN <i>CP</i>	DRAWN BY <i>CP</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED <i>[Signature]</i>	APPROVED <i>[Signature]</i>	DRAWING NO. D6205	REV. A SHEET 1 OF 1
DATE 01.07.17		TITLE CLAMP EXTRUSION	SCALE 1:1
A	01.07.17	NEW ISSUE	

RELEASED
01.08.24**NOTES**

1) D6205-XXX CLAMP EXTRUSION
LENGTH

WHERE XXX IS LENGTH IN INCHES
EG. 3" LONG EXTRUSION: D6205-3

- 2) MATERIAL: 6061-T6 (QQ-A-200/8)
MINIMUM YIELD TENSILE STRENGTH = 35 KSI (241 MPa)
MINIMUM ULTIMATE TENSILE STRENGTH = 38 KSI (262 MPa)
MINIMUM ELONGATION = 8%
- 3) PART IS SYMMETRIC ABOUT CENTERLINE
- 4) ALL DIMENSIONS ARE IN INCHES
- 5) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
- 6) NO TOOLING MARKS
- 7) MANUFACTURED USING BON L DIE # DAA-4

Copyright © 2001 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.